



# Wireless Presentation System

WPS-HD101A / HD312-U / HD304A



Odyssey wireless presentation kit enables wireless signal transmission via multiplatform devices effortlessly up to a range of 30m ( Windows / Android / iOS / Mac ) .

Using USB one touch dongle , no drivers or apps are needed for Windows/ Mac platform devices and supports Airplay for iOS devices.

Supports up to 4 live (quad display)\* of multi-format input/output



## Technical

|                           |                                                                                              |
|---------------------------|----------------------------------------------------------------------------------------------|
| HDMI Compliance           | HDMI 2.2                                                                                     |
| Signal Resolution         | Receiving up to 4K (3840 x 2160 pixels @ 30Hz)<br>Output : Full HD (1920 x1080pixels @ 30Hz) |
| Wireless Frequency        | 2.4G / 5G                                                                                    |
| Wireless Protocol         | IEEE 802.11 n/a/c                                                                            |
| IOS Compatibility         | iOS 9 and above                                                                              |
| Windows Compatibility     | Windows 7 and above                                                                          |
| Mac Compatibility         | Mac 10.11                                                                                    |
| Transmission Range        | Up to 30m ( line of site)                                                                    |
| <b>Devices on display</b> | <b>WPS101A :1 , WPS312U :4 , WPS304A :4</b>                                                  |
| Active Connections        | 16                                                                                           |

## Terminals

|         |                                                                        |
|---------|------------------------------------------------------------------------|
| Input   | 1 x RJ45 [ Network Control/ LAN Admin]<br>2 x Anthena Signal Terminals |
| Outputs | 1 x HDMI Type A<br>1 x 15-pin D-sub [VGA]                              |

## Mechanical

|                         |                                  |
|-------------------------|----------------------------------|
| Dimensions              | 118mm [D] x 179mm [W] x 41mm [H] |
| Net Weight              | 635g                             |
| Power Supply            | AC100 - 240V 50/60Hz             |
| Power Consumption (Max) | 76W                              |
| Operation Temperature   | 32 - 104°F / 0 - 40°C            |
| Storage temperature     | -4 - 140°F / -20 - 60°C          |
| Relative Humidity       | 20 - 90% RH (no condensation)    |